



PANEL CUT-OUT

SPECIFICATION:

- INSULATION RESISTANCE: OVER 100MΩ 500V DC.
- DIELECTRIC STRENGTH: 2000V AC ONE MINUTE.
- Body Materil: Black Glass-Fiber Thermoplastic . UL 94V-2~0

Rating:AC 15A 250V	
Mark	Safety Regulation
RJ	UL
cRJ	CUL
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	CCC
	ENEC



模號: 37,38,39,40,41,42,43,44
61,62,63,64,65,66,67,68.
69,70,71,72,73,74,75,76.

IMPORTANT THIS DRAWING FOR REFERENCE ONLY 注意: 此圖只供參考用



富灣(佛岡)五金電器有限公司
RICH BAY INT'L LTD.
廣東省清遠市佛岡縣城南工業區
South Town Industrial Area of Fogong County
Qing Yuan City Guangdong Province,China
TEL:0763-4289946 FAX:0763-4288096

DRAWN BY	UNIT	UNIT QTY	SCALE	TOLERANCE	PRODUCT NO.	R-301(B00)	REV
	mm	1	1:1	X.XX±0.1 XX.XX±0.2 XXX.XX±0.3			
APPROVED BY	李		羅		ID NO	INTERIM NO.	B
	2010.3.25 小英		2010.3.25 士凱				