



PANEL CUT-OUT

SPECIFICATION:

1. Insulation Resistance: Over 100MΩ at 500V DC.
2. Dielectric strength: 2000V AC 1 Minute.
3. Body Material: Thermoplastic 94V-2~V-0.

Rating:AC 15A 250V	
Mark	Safety Regulation
	CULUS
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE

產品料號	I/O 形式	備註
R-3013S(01)	按鍵黑色印刷 I/O	
R-3013S(02)	按鍵透明紅色帶燈	

DRAWING:C:DG\NEW-R\T\3013S\R-3013S(01,02).DWG

IMPORTANT THIS DRAWING FOR REFERENCE ONLY 注意：此圖只供參考用

<p>富灣股份有限公司 RICH BAY COMPANY LTD. 台北縣樹林市東興街57號 NO. 57, Tung Hsing St., Shu-Lin Town, Taipei Hsien, Taiwan, R. O. C. TEL:886-2-86867781~4 FAX:886-2-86867780 http://www.richbay.com.tw</p>	 DRAWN BY R.D. 97.10.13 李文彬	UNIT	UNIT QTY	SCALE	TOLERANCE X.XX±0.1 XX.XX±0.2 XXX.XX±0.3	PRODUCT NO.	R-3013S (XX)	REV
		mm	1	1:1				
		APPROVED BY	R.D. 97.10.13 戴銘璋	ID NO	081013A10	INTERIM NO.		B
				DESCRIPTION		NEW NO.		