



Thickness	L
1.5	32.2
2.0	32.4
2.5	32.6
3.0	32.8

**RECOMMEND  
PANEL CUT OUT**

**SPECIFICATION:**

1. Insulation Resistance: Over 100MW at 500V DC.
2. Dielectric strength: 2000V AC 1 Minute.
3. Body Material: Thermoplastic 94V-2~V-0.

Rating: AC 15A 250V	
Mark	Safety Regulation
	CULUS
Rating: AC 10A 250V	
Mark	Safety Regulation
	VDE

DRAWING: C:\DG\NEW-R\T\3016\ (00). DWG

**IMPORTANT THIS DRAWING FOR REFERENCE ONLY** 注意：此圖只供參考用

<p>富灣股份有限公司 RICH BAY COMPANY LTD. 台北縣樹林市東興街57號 NO. 57, Tung Hsing St., Shu-Lin Town, Taipei Hsien, Taiwan, R. O. C. TEL: 886-2-86867781~4 FAX: 886-2-86867780 http://www.richbay.com.tw</p>	 DRAWN BY RD 95.10.30 張育誠	UNIT	UNIT QTY	SCALE	TOLERANCE	PRODUCT NO.	R-3016 (00)	REV
		mm	1	1:1	X.XX±0.1 XX.XX±0.2 XXX.XX±0.3	R-3016 (00)		
		APPROVED BY	RD 96.07.09 戴銘璋	ID NO	070612A02	INTERIM NO.		
				DESCRIPTION		NEW NO.		A