



R-302 (00)	R-302 (03)	R-302 (04)
4.8	4.0	6.4
2.7	2.0	2.7
6.6	5.4	8.3
3.0	4.1	3.0

SPECIFICATION:

- Insulation Resistance: Over 100MΩ at 500V DC.
- Dielectric strength: 2000V AC 1 Minute.
- Body Material: Thermoplastic 94V-2~V-0.

Rating:AC 15A 250V	
Mark	Safety Regulation
	UL
	CUL
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	ENEC
	CCC

DRAWING: C:\DG\NEW-R\T\302\R-302(00, 03, 04). DWG

<p>富灣股份有限公司 RICH BAY COMPANY LTD. 台北縣樹林市東興街57號 NO. 57, Tung Hsing St., Shu-Lin Town, Taipei Hsien, Taiwan, R. O. C. TEL:886-2-86867781~4 FAX:886-2-86867780 http://www.richbay.com.tw</p>	 DRAWN BY	UNIT	UNIT QTY	SCALE	TOLERANCE	PRODUCT NO.	R-302 (00)	REV
		mm	1	1:1	X.XX±0.1 XX.XX±0.2 XXX.XX±0.3			
		RD 99.03.26 張育誠	APPROVED BY	RD 99.04.22 戴銘璋	ID NO			
				DESCRIPTION		INTERIM NO.		E
						NEW NO.		