

Product NO.	Description	Notes
RU-515P(C00)	Terminals no plated	
RU-515P(C01)	Extrenal metals Nickel plated	
RU-515P(C02)	Extrenal metals Gold plated	
RU-515P(C09)	All metals Gold plated,expect contact screws	





Notes:

SPECIFICATION:

- Insulation Resistance: Over 100MΩ at 500V DC.
- Dielectric strength: 2000V AC 1 Minute.
- Body Material: Thermoplastic 94V-2~V-0.
- The intended flexible cord:
 - Cord Type - Type SJT
 - Cord Size - NO.12 AWG
 - Total Number of conductors-3 conductors
 - Overall cord diameter -10.6mm'
- Rating:AC 15A 125V

DRAWING:C:DG\NEW-R\S\RU\515P(C00,C01,C02,C09).DWG

IMPORTANT THIS DRAWING FOR REFERENCE ONLY 注意：此圖只供參考用

 富灣股份有限公司 RICH BAY COMPANY LTD. 台北縣樹林市東興街57號 NO. 57, Tung Hsing St.,Shu-Lin Town, Taipei Hsien, Taiwan, R. O. C. TEL:886-2-86867781~4 FAX:886-2-86867780 http://www.richbay.com.tw	 DRAWN BY  RD 98.01.21 張育誠	UNIT	UNIT QTY	SCALE	TOLERANCE	PRODUCT NO.	RU-515P(CXX)	REV
		mm	1	1:1	X.XX±0.1 XX.XX±0.2 XXX.XX±0.3			
		APPROVED BY  RD 98.01.22 戴銘璋	ID NO	090121A01	INTERIM NO.			
		DESCRIPTION		NEW NO.				C